

Electric forklift

Model YD-CPD-201

Technical Specifications & Product Selection



120 grade forklift steel

Front wheel 650-10; Rear wheel 500-8

Handbrake braking, hydraulic system
braking

Door frame material

tire

Braking method

Product code: EXC-1785466050991927

Contents

Use the specification pages first, then review selection conditions, current product views and the final configuration record.

Technical Specifications	03
Technical Specifications – Continued	04
Selection Logic & Application Fit	05
Product Views	06
Product Views – Continued	07
Product Views – Continued	08
Configuration & Component Relationships	09
Configuration & Order Confirmation	10

Reading rule

Use only the values and configuration stated for this exact product. Keep different ratings, options and operating conditions separate; an image does not create an unlisted specification.

CORE PRODUCT DATA

Technical Specifications

Electric forklift / Model YD-CPD-201

Specification	Current product data
Door frame material	120 grade forklift steel
tire	Front wheel 650-10; Rear wheel 500-8
Braking method	Handbrake braking, hydraulic system braking
Rated lifting capacity	2000kg
Vehicle curb weight (including battery)	2800kg
Front tire specification	650-10
Rear tire specification	500-8
Maximum lifting height	3m (two-section mast)
Overall vehicle height (with overhead guard)	2.15m
Vehicle length (to the vertical plane of the forks)	2.5m (excluding forks)
Vehicle width	1.2m
Rated power of the traction motor	5kW
Standard battery voltage/capacity	60V
Attachment	Optional
Charger	220V Six-Stage Smart Charger
Vehicle accessories	Keys, charger, fire extinguisher
Controller brand	Hangzhou Anjener

CORE PRODUCT DATA

Technical Specifications – Continued

Electric forklift / Model YD-CPD-201

Specification	Current product data
Travel motor	Shandong Hart or Wuxi Riel 5kW AC motor
Maebashi	220 suspension type cast steel front axle
Rear axle	Reinforced steel rear axle
Lifting cylinder	Reinforced-seal, wear-resistant dual-cylinder
Chain	7-row roller chain, high load capacity
Steering method	Hydraulic power steering
Turning radius	2.4m, 180 ° in-situ steering
Charging time/voltage	6-8 hours, 220V (optional upgrade)
Continuous working hours	4 hours (optional upgrade)

How to read this data

Review rated load, load center, mast geometry, battery and drive system, turning space and machine dimensions. Do not combine values from different options or infer missing ratings from the product image.

SELECTION & FIT

Selection Logic & Application Fit

Current product scope

This 2-ton electric forklift combines clean electric drive, stable mast lifting, secure tire grip, and protective work features for high-level warehouse operations and material handling.

Step	Selection input
01	Actual load, center and lift height
02	Mast, fork and attachment configuration
03	Battery, charger and duty profile
04	Aisle, floor and turning conditions

Decision boundary

Confirm the exact model, stated technical fields, site relationship and expressly included configuration together. Omitted data is not replaced by an industry average or a nearby model.

CURRENT PRODUCT IMAGES

Product Views

The grouped images provide a concise overview of the current product form, visible systems and configuration relationships.



View scope

Use these views for product recognition, visible configuration and space/interface review. Technical values remain controlled by the specification table and written order.

CURRENT PRODUCT IMAGES

Product Views – Continued

The grouped images provide a concise overview of the current product form, visible systems and configuration relationships.



View scope

Use these views for product recognition, visible configuration and space/interface review. Technical values remain controlled by the specification table and written order.

CURRENT PRODUCT IMAGES

Product Views – Continued

The grouped images provide a concise overview of the current product form, visible systems and configuration relationships.



View scope

Use these views for product recognition, visible configuration and space/interface review. Technical values remain controlled by the specification table and written order.

STRUCTURE & CONFIGURATION

Configuration & Component Relationships

Overhead Guard

High-strength steel structure protects the operator area during normal handling operations.

Operator Seat

Padded seat provides stable support and helps reduce fatigue during extended operation.

Control Assembly

Integrated steering wheel and control levers support clear, accurate machine control.

Body Cover

Streamlined metal panels protect internal systems and maintain a clean exterior.

Traction Battery

High-capacity battery supplies stable power for routine material handling.

Configuration boundary

Component names identify stated or visible product groups only. The exact installed version and inclusion of accessories are confirmed in the applicable order.

FINAL SELECTION RECORD

Configuration & Order Confirmation

Confirmation item	Record
Current product name	Electric forklift
Model	YD-CPD-201
Category	Electric Forklift
Required task / application	
Critical specification fields	
Site, route or installation boundary	
Standard configuration	
Options / accessories included	
Customer / project	
Reviewed by / date	

Release condition

Approve the selection only when identity, technical data, site conditions and the written configuration record agree. A product image or category label does not add an unstated option or rating.